



US006356530B1

(12) **United States Patent**
Tomaszewski et al.

(10) **Patent No.:** US 6,356,530 B1
(45) **Date of Patent:** Mar. 12, 2002

(54) **NEXT HOP SELECTION IN ATM NETWORKS**

(75) **Inventors:** Marek Tomaszewski, Fremont; Ashok Chippa, San Jose; Ethan Spiegel, Mountain View, all of CA (US)

(73) **Assignee:** Cisco Technology, Inc., San Jose, CA (US)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 08/862,915

(22) **Filed:** May 23, 1997

(51) **Int. Cl.⁷** H04L 12/26

(52) **U.S. Cl.** 370/232; 370/397

(58) **Field of Search** 370/395, 397, 370/399, 227, 230, 232, 233, 234

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,131,767 A	12/1978	Weinstein
4,161,719 A	7/1979	Parikh et al.
4,316,284 A	2/1982	Howson
4,397,020 A	8/1983	Howson
4,419,728 A	12/1983	Larson
4,424,565 A	1/1984	Larson
4,437,087 A	3/1984	Petr
4,438,511 A	3/1984	Baran
4,439,763 A	3/1984	Limb
4,445,213 A	4/1984	Baugh et al.
4,446,555 A	5/1984	Devault et al.
4,456,957 A	6/1984	Schieltz
4,464,658 A	8/1984	Thelen
4,499,576 A	2/1985	Fraser
4,506,358 A	3/1985	Montgomery
4,507,760 A	3/1985	Fraser
4,532,626 A	7/1985	Flores et al.
4,644,532 A	2/1987	George et al.
4,646,287 A	2/1987	Larson et al.
4,677,423 A	6/1987	Benvenuto et al.
4,679,189 A	7/1987	Olson et al.

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0 384 758 A2	8/1990
EP	0 431 751 A1	6/1991
EP	0 567 217 A2	10/1993
WO	WO93/07569	4/1993
WO	WO93/07692	4/1993
WO	WO94/01828	1/1994
WO	WO95/20850	8/1995

OTHER PUBLICATIONS

William Stallings, Data and Computer Communications, pp: 329-333, Prentice Hall, Upper Saddle River, New Jersey 07458.

Allen, M., "Novell IPX Over Various WAN Media (IPXW AN)," Network Working Group, RFC 1551, Dec. 1993, pp. 1-22.

Becker, D., "3c589.c: A 3c589 EtherLink3 ethernet driver for linux," becker@CESDIS.gsfc.nasa.gov, May 3, 1994, pp. 1-13.

(List continued on next page.)

Primary Examiner—Melvin Marcelo

Assistant Examiner—D. Trinh


(74) *Attorney, Agent, or Firm*—Blakely, Sokoloff, Taylor & Zafman LLP

(57)

ABSTRACT

The invention provides a method and system for selecting one particular interface between a pair of adjacent nodes in an ATM network for assignment to a call in that network. The cell rate available on each possible interface is examined and compared with the cell rate expected for the call, and one of the interfaces is selected and assigned responsive to those cell rates. (1) The interface can be chosen which preserves the maximum remaining cell rate for future calls. (2) The interface with the highest-speed available link can be chosen, so long as cell rate capacity is available on that interface for the call.

22 Claims, 2 Drawing Sheets



US 6,356,530 B1

Page 2

U.S. PATENT DOCUMENTS

4,679,227 A	7/1987	Hughes-Hartogs	5,280,480 A	1/1994	Pitt et al.
4,723,267 A	2/1988	Jones et al.	5,280,500 A	1/1994	Mazzola et al.
4,731,816 A	3/1988	Hughes-Hartogs	5,283,783 A	2/1994	Nguyen et al.
4,750,136 A	6/1988	Arpin et al.	5,287,103 A	2/1994	Kasprzyk et al.
4,757,495 A	7/1988	Decker et al.	5,287,453 A	2/1994	Robertis
4,763,191 A	8/1988	Gordon et al.	5,291,482 A	3/1994	McHarg et al.
4,769,810 A	9/1988	Eckberg, Jr. et al.	5,305,311 A	4/1994	Lyles
4,769,811 A	9/1988	Eckberg, Jr. et al.	5,307,343 A	4/1994	Bostica et al.
4,771,425 A	9/1988	Baran et al.	5,309,437 A	5/1994	Perlman et al. 730/85.13
4,819,228 A	4/1989	Baran et al.	5,311,509 A	5/1994	Heddes et al.
4,827,411 A	5/1989	Arrowood et al.	5,313,454 A	5/1994	Bustini et al.
4,833,706 A	5/1989	Hughes-Hartogs	5,313,582 A	5/1994	Hendel et al.
4,835,737 A	5/1989	Herrig et al.	5,317,562 A	5/1994	Nardin et al.
4,879,551 A	11/1989	Georgiou et al.	5,319,644 A	6/1994	Liang
4,893,306 A	1/1990	Chao et al.	5,327,421 A	7/1994	Hiller et al.
4,903,261 A	2/1990	Baran et al.	5,331,637 A	7/1994	Francis et al.
4,922,486 A	5/1990	Lidinsky et al.	5,345,445 A	9/1994	Hiller et al.
4,933,937 A	6/1990	Konishi	5,345,446 A	9/1994	Hiller et al.
4,960,310 A	10/1990	Cushing	5,359,592 A	10/1994	Corbalis et al.
4,962,497 A	10/1990	Ferenc et al.	5,361,250 A	11/1994	Nguyen et al.
4,962,532 A	10/1990	Kasirai et al.	5,361,256 A	11/1994	Doeringer et al.
4,965,772 A	10/1990	Daniel et al.	5,361,259 A	11/1994	Hunt et al.
4,970,678 A	11/1990	Sladowski et al.	5,365,524 A	11/1994	Hiller et al.
4,979,118 A	12/1990	Kheradpir 364/436	5,367,517 A	11/1994	Cidon et al.
4,980,897 A	12/1990	Decker et al.	5,371,852 A	12/1994	Altanasio et al.
4,991,169 A	2/1991	Davis et al.	5,386,567 A	1/1995	Lien et al.
5,003,595 A	3/1991	Collins et al.	5,390,170 A	2/1995	Sawant et al.
5,014,265 A	5/1991	Hahne et al.	5,390,175 A	2/1995	Hiller et al.
5,020,058 A	5/1991	Holden et al.	5,394,394 A	2/1995	Crowther et al.
5,033,076 A	7/1991	Jones et al.	5,394,402 A	2/1995	Ross
5,054,034 A	10/1991	Hughes-Hartogs	5,400,325 A	3/1995	Chatwani et al.
5,059,925 A	10/1991	Weisbloom	5,408,469 A	4/1995	Opher et al.
5,072,449 A	12/1991	Enns et al.	5,416,842 A	5/1995	Aziz
5,088,032 A	2/1992	Bosack	5,422,880 A	6/1995	Heitkamp et al.
5,095,480 A	3/1992	Fenner	5,422,882 A	6/1995	Hiller et al.
RE33,900 E	4/1992	Howson	5,423,002 A	6/1995	Hart
5,115,431 A	5/1992	Williams et al.	5,426,636 A	6/1995	Hiller et al.
5,115,495 A *	5/1992	Tsuchiya et al. 709/239	5,428,607 A	6/1995	Hiller et al.
5,119,367 A *	6/1992	Kawakatsu et al. 370/232	5,430,715 A	7/1995	Corbalis et al.
5,128,926 A *	7/1992	Perlman et al. 370/248	5,430,729 A	7/1995	Rahnema
5,128,945 A	7/1992	Enns et al.	5,442,457 A	8/1995	Najafi
5,136,580 A	8/1992	Videloock et al.	5,442,630 A	8/1995	Gagliardi et al.
5,166,930 A	11/1992	Braff et al.	5,452,294 A *	9/1995	Natarajan 370/351
5,189,662 A *	2/1993	Kleine-Altekamp 370/227	5,452,297 A	9/1995	Hiller et al.
5,199,049 A	3/1993	Wilson	5,473,599 A	12/1995	Li et al.
5,206,886 A	4/1993	Bingham	5,473,607 A	12/1995	Hausman et al.
5,208,811 A	5/1993	Kashio et al.	5,477,541 A	12/1995	White et al.
5,212,686 A	5/1993	Joy et al.	5,485,455 A	1/1996	Dobbins et al.
5,224,099 A	6/1993	Corbalis et al.	5,490,140 A	2/1996	Abensour et al.
5,226,120 A	7/1993	Brown et al.	5,490,258 A	2/1996	Fenner
5,228,062 A	7/1993	Bingham	5,491,687 A	2/1996	Christensen et al.
5,229,994 A	7/1993	Balzano et al.	5,491,804 A	2/1996	Heath et al.
5,233,604 A *	8/1993	Ahmadi et al. 370/238	5,497,368 A	3/1996	Reijnierse et al.
5,237,564 A	8/1993	Lespagnol et al.	5,504,747 A	4/1996	Sweasey
5,241,682 A	8/1993	Bryant et al.	5,509,006 A	4/1996	Wilford et al.
5,243,342 A	9/1993	Kattemalalavadi et al.	5,517,494 A	5/1996	Green
5,243,596 A	9/1993	Port et al.	5,519,704 A	5/1996	Farinacci et al.
5,247,516 A	9/1993	Bernstein et al.	5,519,858 A	5/1996	Walton et al. 395/600
5,249,178 A	9/1993	Kurano et al.	5,526,489 A	6/1996	Nilakantan et al.
5,253,251 A	10/1993	Aramaki	5,530,963 A	6/1996	Moore et al.
5,255,291 A	10/1993	Holden et al.	5,535,195 A	7/1996	Lee
5,260,933 A	11/1993	Rouse	5,539,734 A	7/1996	Burwell et al.
5,260,978 A	11/1993	Fleischer et al.	5,541,911 A	7/1996	Nilakantan et al.
5,268,592 A	12/1993	Bellamy et al.	5,546,370 A	8/1996	Ishikawa
5,268,900 A	12/1993	Hluchyj et al.	5,555,244 A	9/1996	Gupta et al.
5,271,004 A	12/1993	Proctor et al.	5,561,669 A	10/1996	Lenney et al.
5,274,631 A	12/1993	Bhardwaj	5,583,862 A	12/1996	Callon
5,274,635 A	12/1993	Rahman et al.	5,592,470 A	1/1997	Rudrapatna et al.
5,274,643 A	12/1993	Fisk	5,598,581 A	1/1997	Daines et al.
5,280,470 A	1/1994	Buhrke et al.	5,600,798 A	2/1997	Cherukuri et al.
			5,604,868 A	2/1997	Komine et al.

5,608,726 A	3/1997	Virgile	
5,617,417 A	4/1997	Sathe et al.	
5,617,421 A	4/1997	Chin et al.	
5,630,125 A	5/1997	Zellweger	
5,631,908 A	5/1997	Saxe	
5,632,021 A	5/1997	Jennings et al.	
5,634,010 A	5/1997	Ciscon et al.	
5,638,359 A	6/1997	Peltola et al.	
5,644,718 A	7/1997	Belove et al.	
5,659,684 A	8/1997	Giovannoni et al.	
5,666,353 A	9/1997	Klausmeier et al.	
5,673,265 A	9/1997	Gupta et al.	
5,678,006 A	10/1997	Valizadeh et al.	
5,680,116 A	10/1997	Hashimoto et al.	
5,684,797 A	11/1997	Aznar et al.	
5,687,324 A	11/1997	Green et al.	
5,689,506 A	11/1997	Chiussi et al.	
5,694,390 A	12/1997	Yamato et al.	
5,724,351 A	3/1998	Chao et al.	
5,748,186 A	5/1998	Raman	
5,748,617 A	5/1998	McLain, Jr.	
5,754,547 A	5/1998	Nakazawa	
5,802,054 A	9/1998	Bellenger	
5,835,710 A	11/1998	Nagami et al.	
5,854,903 A	12/1998	Morrison et al.	
5,856,981 A	1/1999	Voelker	
5,892,924 A	4/1999	Lyon et al.	395/200.75
5,898,686 A	4/1999	Virgile	
5,903,559 A	5/1999	Acharya et al.	
6,167,030 A	* 12/2000	Kilkki et al.	370/236

OTHER PUBLICATIONS

Chowdhury, et al., "Alternative Bandwidth Allocation Algorithms for Packet Video in ATM Networks," INFOCOM 1992, PP. 1061-1068.

Doeringer, W., "Routing on Longest-Matching Prefixes," IEEE/ACM Transactions in Networking, vol. 4, No. 1, Feb. 1996, pp. 86-97.

Esaki, et al., "Datagram Delivery in an ATM-Internet," 2334b IEICE Transactions on Communications, Mar. 1994, No. 3, Tokyo, Japan.

IBM Corporation, "Method and Apparatus for the Statistical Multiplexing of Voice, Data and Image Signals," IBM Technical Disclosure Bulletin, No. 6, Nov. 1992, pp. 409-411.

Pei, et al., "Putting Routing Tables in Silicon," IEEE Network Magazine, Jan. 1992, pp. 42-50.

Perkins, D., "Requirements for an Internet Standard Point-to-Point Protocol," Network Working Group, RFC 1547, Dec. 1993, pp. 1-19.

Simpson, W., "The Point-to-Point Protocol (PPP)," Network Working Group, RFC 1548, Dec. 1993, pp. 1-53.

Tsuchiya, P. F., "A Search Algorithm for Table Entries with Non-Contiguous Wildcarding," Abstract, Bellcore.

Zhang, et al., "Rate-Controlled Static-Priority Queueing," INFOCOM 1993, pp. 227-236.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

1

NEXT HOP SELECTION IN ATM NETWORKS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to ATM networks.

2. Related Art

In known ATM systems, each call is routed in a virtual circuit which is specified by the sending node. This circuit includes a plurality of ATM switches in a virtual circuit from the sending node to the receiving node. If two adjacent nodes in the virtual circuit have more than one interface connecting them, one of the plurality of interfaces must be specifically chosen and assigned to the call.

In some instances, the interface is specified by the sending node. However, when the particular interface is not specified by the sending node, the two adjacent nodes must select one of the plurality of interfaces. In known ATM systems, one interface is selected by round-robin assignment. While this method is effective to unambiguously select one of the plurality of interfaces, it has the drawback that the selected interface can be inappropriate for optimal call routing.

Accordingly, it would be desirable to provide a method and system for selecting one particular interface, which is more appropriate for optimal call routing. This advantage is achieved in an embodiment of the invention in which relative bandwidth or another characteristic of the plurality of interfaces, and in which relative size or another characteristic of the call, are examined and taken into account when one interface is specifically chosen and assigned to the call.

SUMMARY OF INVENTION

The invention provides a method and system for selecting one particular interface between a pair of adjacent nodes in an ATM network for assignment to a call in that network. The cell rate available on each possible interface is examined and compared with the cell rate expected for the call, and one of the interfaces is selected and assigned responsive to those cell rates.

In a first preferred embodiment, the interface is chosen which preserves the maximum remaining cell rate for future calls. In a second preferred embodiment, the interface with the highest-speed available link is chosen, so long as cell rate capacity is available on that interface for the call.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a block diagram of an ATM network.

FIG. 2 shows a process flow diagram of a first method for selecting an interface for assignment to a call.

FIG. 3 shows a process flow diagram of a second method for selecting an interface for assignment to a call.

FIG. 4 shows a process flow diagram of a third method for selecting an interface for assignment to a call.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following description, a preferred embodiment of the invention is described with regard to preferred process steps and data structures. Those skilled in the art would recognize after perusal of this application that embodiments of the invention can be implemented using general purpose switching processors or special purpose switching processors or other circuits adapted to particular process steps and

2

data structures described herein, and that implementation of the process steps and data structures described herein would not require undue experimentation or further invention.

Inventions described herein can be used in conjunction with inventions described in the following application:

Application No. 08/863,031, filed May 23, 1997, in the name of the same inventors, entitled Call Size Feedback on PNNI Operation, which issued as U.S. Pat. No. 6,122,272 on Sep. 19, 2000 and is assigned to the same assignee as the present application.

This application is hereby incorporated by reference as if fully set forth herein.

ATM Network Including Multiple Interfaces Between Adjacent Nodes

FIG. 1 shows a block diagram of an ATM network.

An ATM network 100 includes a plurality of ATM nodes 110, each of which is capable of transmitting ATM cells from a sending node 110 to a designated receiving node 110. Each pair of adjacent nodes 110 has at least one, and possibly more than one, interface 120. Each interface 120 is capable of transmitting ATM cells from a first adjacent node 110 to a second adjacent node 110.

When an incoming call is received at the sending node 110, that incoming call specifies a virtual circuit for the call, including the sending node 110, the designated receiving node 110, and a designated sequence of intermediate nodes 110, for transmitting ATM cells for the call from the sending node 110 to the receiving node 110. The incoming call may also specify other information about the call, such as a required cell transmission rate for the call.

When the virtual circuit for the call is set up, there may be one or more pairs of adjacent nodes 110 which have a plurality of interfaces 120 therebetween. In some cases, the incoming call will specify which of the interfaces 120 is to be included in the virtual circuit. In those case where the incoming call does not so specify, one of the methods shown herein is used to select one of the interfaces 120 for inclusion in the virtual circuit and thus for assignment to the call.

In preferred embodiments, the cell rate available on each possible interface is examined and compared with the cell rate expected for the call, and one of the interfaces is selected and assigned responsive to those cell rates.

First Method for Selecting Interface

FIG. 2 shows a process flow diagram of a first method for selecting an interface for assignment to a call.

A first method 200 applies to CBR (constant bit rate), RT-VBR (real time variable bit rate), and NRT-VBR (non-real time variable bit rate) traffic classes in an ATM network. The first method 200 includes the steps 211 through 214.

At a step 211, the method 200 identifies a plurality of interfaces 120 between the first adjacent node 110 and the second adjacent node 110.

At a step 212, the method 200 selects, from the interfaces 120 identified in the step 211, the ones which have sufficient AvCR (available cell rate) for the incoming call.

At a step 213, the method 200 orders the interfaces 120 selected in the step 212 in increasing order of AvCR.

At a step 214, the method 200 selects the first interface 120 in an ordered list generated by the step 213.

The first method thus chooses the interface which preserves the maximum remaining cell rate for future calls.

Second Method for Selecting Interface

FIG. 3 shows a process flow diagram of a second method for selecting an interface for assignment to a call.

A second method 300 also applies to CBR (constant bit rate), RT-VBR (real time variable bit rate), and NRT-VBR (non-real time variable bit rate) traffic classes in an ATM network. The second method 300 includes the steps 311 through 313.

3

At a step 311 (like the step 211 performed by the method 200), the method 300 identifies a plurality of interfaces 120 between the first adjacent node 110 and the second adjacent node 110.

At a step 312, the method 300 orders the interfaces 120 identified in the step 311 in decreasing order of Maximum Cell Rate.

At a step 313, the method 300 selects the first interface 120 in an ordered list generated by the step 312.

The second method 300 thus chooses the interface with the highest-speed available link is chosen, so long as cell rate capacity is available on that interface for the call.

Third Method for Selecting Interface

FIG. 4 shows a process flow diagram of a third method for selecting an interface for assignment to a call.

A third method 400 applies to ABR (available bit rate) and UBR (unspecified bit rate) traffic classes in an ATM network. The third method 400 includes the steps 411 through 414.

At a step 411 (like the step 211 performed by the method 200), the method 400 identifies a plurality of interfaces 120 between the first adjacent node 110 and the second adjacent node 110.

At a step 412, for each interface 120_i identified in the step 411, the method 400 determines the Available Cell Rate AvCR(i). The available cell rate is determined by subtracting, from the Maximum Cell Rate, the amount of bandwidth already reserved for that interface 120.

At a step 413, for each interface 120_i identified in the step 411, the method 400 determines the ratio AvCR(i)/(N_i+1), where N_i is the number of actual "best effort" virtual circuits which are using the interface 120 i.

At a step 414, the method 400 orders the interfaces identified in the step 411 in decreasing order of the ratio determined in the step 413.

At a step 415, the method 400 selects the first interface 120 in an ordered list generated by the step 414.

The third method 400 thus chooses the interface which best balances the load of multiple calls across multiple interfaces, after subtracting reserved bandwidth from each interface.

Alternative Embodiments

Although preferred embodiments are disclosed herein, many variations are possible which remain within the concept, scope, and spirit of the invention, and these variations would become clear to those skilled in the art after perusal of this application.

What is claimed is:

1. A method comprising:

receiving a request for a virtual circuit in a node of a switching network;

retrieving an available cell rate to accommodate said virtual circuit for each interface of a plurality of interfaces between said node and a second node of said switching network, said second node being adjacent to said first node;

selecting said each interface having said available cell rate higher than a transmission cell rate for said virtual circuit; and

selecting an optimum interface from said each interface selected for inclusion in said virtual circuit, said optimum interface having a lowest available cell rate of said available cell rate of said each interface selected.

2. The method according to claim 1, wherein said switching network is an ATM network accommodating a constant bit rate (CBR) traffic class.

3. The method according to claim 1, wherein said switching network is an ATM network accommodating a real time variable bit rate (RT-VBR) traffic class.

4

4. The method according to claim 1, wherein said switching network is an ATM network accommodating a non real time variable bit rate (NTR-VBR) traffic class.

5. A method comprising:

receiving a request for a virtual circuit in a node of a switching network;

retrieving an available cell rate to accommodate said virtual circuit for each interface of a plurality of interfaces between said node and a second node of said switching network, said second node being adjacent to said first node, said each interface having a transmission speed rate;

selecting said each interface having said available cell rate higher than a transmission cell rate for said virtual circuit; and

selecting an optimum interface from said each interface selected for inclusion in said virtual circuit, said optimum interface having a highest transmission speed rate of said transmission speed rate of said each interface selected.

6. The method according to claim 5, wherein said switching network is an ATM network accommodating a constant bit rate (CBR) traffic class.

7. The method according to claim 5, wherein said switching network is an ATM network accommodating a real time variable bit rate (RT-VBR) traffic class.

8. The method according to claim 5, wherein said switching network is an ATM network accommodating a non real time variable bit rate (NTR-VBR) traffic class.

9. A method comprising:

receiving a request for a virtual circuit in a node of a switching network;

retrieving an available cell rate to accommodate said virtual circuit for each interface of a plurality of interfaces between said node and a second node of said switching network, said second node being adjacent to said first node;

calculating a ratio for said each interface, as said available cell rate divided by at least one existent virtual circuit in said each interface; and

selecting an optimum interface from said each interface for inclusion in said virtual circuit, said optimum interface having a highest ratio of said ratio of said each interface.

10. The method according to claim 9, wherein said switching network is an ATM network accommodating an available bit rate (ABR) traffic class.

11. The method according to claim 9, wherein said switching network is an ATM network accommodating an unspecified bit rate (UBR) traffic class.

12. A system comprising:

a first node in a switching network to receive a request for a virtual circuit; and

a second node in said switching network, adjacent to said first node and coupled to said first node through a plurality of interfaces;

said first node to retrieve an available cell rate to accommodate said virtual circuit for each interface of said plurality of interfaces, to select said each interface having said available cell rate higher than a transmission cell rate for said virtual circuit, and to select an optimum interface from said each interface selected, said optimum interface having a lowest available cell rate of said available cell rate of said each interface selected.

5

13. The system according to claim 12, wherein said switching network is an ATM network accommodating a constant bit rate (CBR) traffic class.

14. The system according to claim 12, wherein said switching network is an ATM network accommodating a real time variable bit rate (RT-VBR) traffic class. 5

15. The system according to claim 12, wherein said switching network is an ATM network accommodating a non real time variable bit rate (NTR-VBR) traffic class.

16. A system comprising:

a first node in a switching network to receive a request for a virtual circuit; and 10

a second node in said switching network, adjacent to said first node and coupled to said first node through a plurality of interfaces; 15

said first node to retrieve an available cell rate to accommodate said virtual circuit for each interface of said plurality of interfaces, said each interface having a transmission speed rate, to select said each interface having said available cell rate higher than a transmission cell rate for said virtual circuit, and to select an optimum interface from said each interface selected, said optimum interface having a highest transmission speed rate of said transmission speed rate of said each interface selected. 20 25

17. The system according to claim 16, wherein said switching network is an ATM network accommodating a constant bit rate (CBR) traffic class.

6

18. The system according to claim 16, wherein said switching network is an ATM network accommodating a real time variable bit rate (RT-VBR) traffic class.

19. The system according to claim 16, wherein said switching network is an ATM network accommodating a non real time variable bit rate (NTR-VBR) traffic class.

20. A system comprising:

a first node in a switching network to receive a request for a virtual circuit; and

a second node in said switching network, adjacent to said first node and coupled to said first node through a plurality of interfaces;

said first node to retrieve an available cell rate to accommodate said virtual circuit for each interface of said plurality of interfaces, to calculate a ratio for said each interface, as said available cell rate divided by at least one existent virtual circuit in said each interface, and to select said optimum interface having a highest ratio of said ratio of said each interface.

21. The system according to claim 20, wherein said switching network is an ATM network accommodating an available bit rate (ABR) traffic class.

22. The system according to claim 20, wherein said switching network is an ATM network accommodating an unspecified bit rate (UBR) traffic class.

* * * * *